



180° Silicone Turbocharger Elbows

Uses: In high temperature Turbocharger application.

Features:

- 3/4 plies or custom ply woven Aramid (Nomex) reinforcement to meet burst pressure.
- Working Temperature -65°C to + 260°C.
- Flexible to absorb system vibration
- Fluorocarbon / Fluorosilicone liner used for oil and petrochemicals resistance.
- Highly Flexible.
- Excellent Ozone UV resistance.

Sizes

Sr. No.	Hose ID, (mm)	Leg length 1 (mm)	Leg length 2 (mm)	Wall Thickness (mm)	No. of Plies
1	6.5	100	100	4	3
2	8.0	100	100	4	3
3	9.5	100	100	4	3
4	11	100	100	4	3
5	13	100	100	4	3
6	16	100	100	4	3
7	19	100	100	4	3
8	22	100	100	4	3
9	25	100	100	4	3
10	28	100	100	4	3
11	30	100	100	4	3
12	32	100	100	4	3
13	35	100	100	4	3
14	38	100	100	4	3
15	41	100	100	4	3
16	45	100	100	4	3
17	48	100	100	4	3
18	51	100	100	5	4
19	54	100	100	5	4
20	57	100	100	5	4
21	60	100	100	5	4
22	63	100	100	5	4
23	65	100	100	5	4
24	68	100	100	5	4
25	70	100	100	5	4
26	76	100	100	5	4
27	80	100	100	5	4

28	83	100	100	5	4
29	90	100	100	5	4
30	102	100	100	5	4
31	114	100	100	5	4
32	127	100	100	5	4
33	152	100	100	5	4

www.unitedrubber.net