



Standard 45 ° Silicone Turbocharger Elbows

Uses: In high temperature Turbocharger application.

Features:

- 3/4 plies or custom ply woven Aramid (Nomex) reinforcement to meet burst pressure.
- Working Temperature -65°C to + 260°C.
- Flexible to absorb system vibration
- Fluorocarbon / Fluorosilicone liner used for oil and petrochemicals resistance.
- Highly Flexible.
- Excellent Ozone UV resistance.

Sizes

Sr. No.	Hose ID, mm	Leg length 1 (mm)	Leg length 2 (mm)	Wall Thickness (mm)	No. of Plies
1	6.5	150	150	4	3
2	8.0	150	150	4	3
3	9.5	150	150	4	3
4	11	150	150	4	3
5	13	150	150	4	3
6	16	150	150	4	3
7	19	150	150	4	3
8	22	150	150	4	3
9	25	150	150	4	3
10	28	150	150	4	3
11	30	150	150	4	3
12	32	150	150	4	3
13	35	150	150	4	3
14	38	150	150	4	3
15	40	150	150	4	3
16	45	150	150	4	3
17	48	150	150	4	3
18	51	150	150	5	4
19	54	150	150	5	4
20	57	150	150	5	4
21	60	150	150	5	4
22	63	150	150	5	4
23	65	150	150	5	4
24	68	150	150	5	4
25	70	150	150	5	4
26	76	150	150	5	4
27	80	150	150	5	4

28	83	150	150	5	4
29	90	150	150	5	4
30	102	150	150	5	4
31	114	150	150	5	4
32	127	150	150	5	4
33	152	150	150	5	4

www.unitedrubber.net