



Silicone 90° Reducer (Turbocharger)

Uses: In high temperature Turbocharger application.

Features:

- 3/4 plies or custom ply woven Aramid (Nomex) reinforcement to meet burst pressure.
- Working Temperature -65°C to + 260°C.
- Flexible to absorb system vibration
- Fluorocarbon / Fluorosilicone liner used for oil and petrochemicals resistance.
- Highly Flexible.
- Excellent Ozone UV resistance

Sizes

Sr. No.	Hose ID 1, (mm)	Hose ID 2 (mm)	length (mm)	Wall Thickness (mm)	No. of Plies
1	16	13	127	4	3
2	19	13	127	4	3
3	19	16	127	4	3
4	22	16	127	4	3
5	22	19	127	4	3
6	25	16	127	4	3
7	25	19	127	4	3
8	32	25	127	4	3
9	35	25	127	4	3
10	35	32	127	4	3
11	38	25	127	4	3
12	38	32	127	4	3
13	38	35	127	4	3
14	51	38	127	5	4
15	51	45	127	5	4
16	57	51	127	5	4
17	60	51	127	5	4
18	63	51	127	5	4
19	70	51	127	5	4
20	70	60	127	5	4
21	70	63	127	5	4
22	76	51	127	5	4
23	76	60	127	5	4
24	76	63	127	5	4
25	76	67	127	5	4
26	80	70	127	5	4
27	90	76	127	5	4

28	90	80	127	5	4
29	102	76	127	5	4
30	102	89	127	5	4

www.unitedrubber.net