



Silicone Standard Straight Coolant Hose

Uses: In heavy duty high temperature and pressure coolant connection in Diesel Engine.

Features:

- 3/4/5 plies Silicone Polyester reinforcement construction.
- Application Temperature - -55°C to + 180°C
- Material Properties and Hose performance as per SAE J20 R1 H1, Class A material.
- EC (Electro-chemical) Resistance
- Ozone and UV Resistance.
- Available in Blue, Red & Black Colour

Sizes

Sr. No.	Hose ID, (mm)	Wall Thickness (mm)	Length (meter)	No. of Plies
1	6.5	4	1, 2, 3, 4	3
2	8.0	4	1, 2, 3, 4	3
3	9.5	4	1, 2, 3, 4	3
4	11	4	1, 2, 3, 4	3
5	13	4	1, 2, 3, 4	3
6	16	4	1, 2, 3, 4	3
7	19	4	1, 2, 3, 4	3
8	22	4	1, 2, 3, 4	3
9	25	4	1, 2, 3, 4	3
10	28	4	1, 2, 3, 4	3
11	30	4	1, 2, 3, 4	3
12	32	4	1, 2, 3, 4	3
13	35	4	1, 2, 3, 4	3
14	38	4	1, 2, 3, 4	3
15	40	4	1, 2, 3, 4	3
16	45	4	1, 2, 3, 4	3
17	48	4	1, 2, 3, 4	3
18	51	5	1, 2, 3, 4	4
19	54	5	1, 2, 3, 4	4
20	57	5	1, 2, 3, 4	4
21	60	5	1, 2, 3, 4	4
22	63	5	1, 2, 3, 4	4
23	65	5	1, 2, 3, 4	4

24	68	5	1, 2, 3, 4	4
25	70	5	1, 2, 3, 4	4
26	76	5	1, 2, 3, 4	4
27	80	5	1, 2, 3, 4	4
28	83	5	1, 2, 3, 4	4
29	90	5	1, 2, 3, 4	4
30	102	5	1, 2, 3, 4	4
31	114	5	1, 2, 3, 4	4
32	127	5	1, 2, 3, 4	4
33	152	5	1, 2, 3, 4	4

www.unitedrubber.net