



Silicone Straight Reducer (Coolant)

Uses: In Coolant Application.

Features:

- 3/4 plies or custom ply polyester knitted fabric reinforcement
- Custom ply configuration to meet desired flexibility & burst pressure requirement.
- Working Temperature -65°C to + 180°C.
- Material properties & performance as per SAE J20 R1, Class A.
Excellent Ozone and UV Resistance

Sizes

Sr.	HoseID1, (m m)	Hose ID 2 (mm)	length (m m)	Wall Thickness (mm)	No. of Pli es
1	16	13	127	4	3
2	19	13	127	4	3
3	19	16	127	4	3
4	22	16	127	4	3
5	22	19	127	4	3
6	25	16	127	4	3
7	25	19	127	4	3
8	28	22	127	4	3
9	28	25	127	4	3
10	32	25	127	4	3
11	32	28	127	4	3
12	35	25	127	4	3
13	35	28	127	4	3
14	35	32	127	4	3
15	38	22	127	4	3
16	38	25	127	4	3
17	38	28	127	4	3
18	38	32	127	4	3
19	38	35	127	4	3
20	40	35	127	4	3
21	45	32	127	4	3
22	45	38	127	4	3
23	51	38	127	5	4
24	51	45	127	5	4

25	54	51	127	5	4
26	57	51	127	5	4
27	60	50	127	5	4
28	63	51	127	5	4
29	70	50	127	5	4
30	70	57	127	5	4
31	70	60	127	5	4
32	76	51	127	5	4
33	76	60	127	5	4
34	76	63	127	5	4
35	76	67	127	5	4
36	80	70	127	5	4
37	90	76	127	5	4
38	90	80	127	5	4
39	102	76	127	5	4
40	114	89	127	5	4
41	114	102	127	5	4
42	127	102	127	5	4
43	127	114	127	5	4

www.unitedrubber.net