



Silicone Standard Straight Turbocharge Hose

Uses: In high operating temperature of Diesel Engine Turbocharger.

Features:

- 3/4/5 plies Silicone Aramid (Nomex) reinforced construction.
- Special grade Silicone used to resistant very high temperature.
- Working Temperature -65°C to + 260°C.
- Flexible to absorb system vibration
- Fluorocarbon / Fluorosilicone liner used for oil and petrochemicals resistance.
- Ozone & UV resistance.
- Available with Heat Protection Sleeve for very high ambient temperature

Sizes

Sr. No.	Hose ID, (mm)	Wall Thickness (mm)	Length (meter)	No. of Plies
1	6.5	4	1, 2, 3, 4	3
2	8.0	4	1, 2, 3, 4	3
3	9.5	4	1, 2, 3, 4	3
4	11	4	1, 2, 3, 4	3
5	13	4	1, 2, 3, 4	3
6	16	4	1, 2, 3, 4	3
7	19	4	1, 2, 3, 4	3
8	22	4	1, 2, 3, 4	3
9	25	4	1, 2, 3, 4	3
10	28	4	1, 2, 3, 4	3
11	30	4	1, 2, 3, 4	3
12	32	4	1, 2, 3, 4	3
13	35	4	1, 2, 3, 4	3
14	38	4	1, 2, 3, 4	3
15	40	4	1, 2, 3, 4	3
16	45	4	1, 2, 3, 4	3
17	48	4	1, 2, 3, 4	3
18	51	5	1, 2, 3, 4	4
19	54	5	1, 2, 3, 4	4
20	57	5	1, 2, 3, 4	4
21	60	5	1, 2, 3, 4	4
22	63	5	1, 2, 3, 4	4
23	65	5	1, 2, 3, 4	4
24	68	5	1, 2, 3, 4	4
25	70	5	1, 2, 3, 4	4
26	76	5	1, 2, 3, 4	4
27	80	5	1, 2, 3, 4	4
28	83	5	1, 2, 3, 4	4
29	90	5	1, 2, 3, 4	4

30	102	5	1, 2, 3, 4	4
31	114	5	1, 2, 3, 4	4
32	127	5	1, 2, 3, 4	4
33	152	5	1, 2, 3, 4	4

www.unitedrubber.net